



16-Port Gigabit Ethernet Switch

16-Port RJ45 10/100/1000 Mbps, IEEE 802.3az Energy Efficient Ethernet, Desktop, 10" and 19" Rackmount

Part No.: 561068

EAN-13: 0766623561068 | UPC: 766623561068

Boost your network speed

The Intellinet Network Solutions Gigabit Ethernet Switch offers an array of features while providing superior network throughput.

Extreme Flexibility

Sixteen 10/100/1000 Mbps auto-sensing ports automatically detect optimal network speeds.

Extreme Throughput

With a backplane speed of 32 Gbps, there is plenty of performance available for your computers, servers and other networking devices.

Includes 10" and 19" rackmount brackets

With the included brackets, you can mount this switch in a classic 19" rack or a more compact 10" cabinet.

Features:

- 10/100/1000 auto-sensing ports automatically detect optimal network speeds
- All RJ45 ports with Auto-MDIX (auto uplink) support
- For use on desktop or mounted in standard 19" rack

INTELLINET®

intellinet-network.com

- Supports NWay auto-negotiation
- Store and forward switching architecture
- Full/half duplex operation
- Supports 802.3x flow control for full duplex mode and collision-based backpressure for half duplex mode
- Green Ethernet power-saving technology deactivates unused ports and adjusts power levels based on the cable length
- 32 Gbps switch fabric
- Supports jumbo frames up to 9 kBytes
- Supports up to 8192 MAC address entries
- 512 kBytes buffer memory
- Supports MAC address auto-learning and auto-aging
- Fanless design ideal for silent operation
- Includes 10" and 19" rackmount brackets
- Fully NDAA-compliant
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3az (Energy Efficient Ethernet EEE)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 10Base-T Cat3, 4, 5 UTP/STP RI45
 - 100Base-TX Cat5 UTP/STP RI45
 - 1000Base-T Cat5e UTP/STP RJ45
- Packet filter/forwarding rate:
- 1,488,000 pps (1000 Mbps)
- 148,800 pps (100 Mbps)
- 14,880 pps (10 Mbps)
- MAC address table: 8192 entries
- Backplane speed: 32 Gbps
- Switch architecture: store and forward
- 16 RJ45 Gigabit Ethernet ports
- Certifications: FCC Class A, CE, UKCA, NDAA

LEDs

- Power
- Link/Activity per port

Power

• Internal power supply: 100 - 240 VAC, 50/60 Hz



intellinet-network.com

• Power consumption: 9.1 watts (maximum)

Environmental

- Metal housing
- Dimensions: 215 (W) x 133 (L) x 44 (H) [mm] / 8.46 (W) x 5.24 (L) x 1.73 (H) [in]
- Weight: 0.94 kg (2 lbs.)
- Operating temperature: 0 40°C (32 104°F)
- Operating humidity: 10 90% RH, non-condensing
- Storage temperature: -20 70°C (-4 158°F)

Package Contents

- 16-Port Gigabit Ethernet Switch
- 10" & 19" rackmount brackets
- Power cable
- Instructions















intellinet-network.com