

UniFi[®] Network



UniFi Switch 24

USW-24 is a managed Layer 2 switch with (24) Gigabit Ethernet ports and (2) SFP ports. Its compact 7.9" depth and fanless design allow it to be placed in any workspace, and the 1.3" touchscreen provides current switch states and the necessary information you need for quick diagnosis.



Mechanical

| | |
|--------------------|---|
| Dimensions | 442.4 x 200 x 43.7 mm (17.42 x 7.87 x 1.72") |
| Weight | Without Mount: 2.70 kg (5.95 lb) With Mount: 2.79 kg (6.15 lb) |
| Enclosure Material | SGCC Steel |

Hardware

| | |
|-------------------------------|---|
| Total Non-Blocking Throughput | 26 Gbps |
| Switching Capacity | 52 Gbps |
| Forwarding Rate | 38.69 Mpps |
| Max. Power Consumption | 25W |
| Power Method | Universal AC Input: 100-240VAC, 50/60 Hz |
| Power Supply | AC/DC, Internal, 36W |
| Networking Interfaces | (24) 10/100/1000 Mbps Ethernet RJ45 Ports (2) 1 Gbps SFP Ports |
| Management Interface | Ethernet In-Band |
| Modes | SMB Layer 2 Gigabit Ethernet Switch |
| ESD/EMP Protection | Air: ± 16 kV, Contact: ± 12 kV |
| Operating Temperature | -5 to 40° C (23 to 104° F) |
| Operating Humidity | 10 - 90% Noncondensing |
| Certifications | CE, FCC, IC |

LEDs

| | |
|----------|--|
| System | (1) Bootup Animation: Bootup in Progress Firmware Upgrade Icon: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted |
| Ethernet | Green: 1G, Amber: 10/100 Mbps |
| SFP | Green: 1G |



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.